










Specifications

-  bottom mount
-  18 mm / 0.71 in.
-  dynamic up to 68 kg / 150 lbs. (full extension)
dynamic up to 53 kg / 120 lbs. (over extension)
-  solid synthetic rollers
-  stainless steel 1.4509 / 441
-  -25 °C to +80 °C
-13 °F to +176 °F

Characteristics

- high lateral stability
- cabinet and drawer profile with screw holes
- ideal running characteristic and smoothness of running through integrated progressive action
- integrated safety clip
- dual-sided captive profile
- synthetic stop
- self-closing

Dimensions



Length		Extension		Extension		Weight		Item No.	Item No.
		full extension		over extension		per set		full extension	over extension
mm	inch	mm	inch	mm	inch	kg	lbs.		
350	13.78	335	13.19	410	16.14	*	*	*	*
400	15.75	385	15.16	460	18.11	1.95	4.29	7941	*
450	17.72	435	17.13	510	20.08	2.21	4.87	7942	*
500	19.69	485	19.09	560	22.05	2.46	5.43	7943	*
550	21.65	535	21.06	610	24.02	2.72	6.00	7944	81413
600	23.62	585	23.03	660	25.98	2.94	6.48	7945	*
650	25.59	635	25.00	710	27.95	3.17	6.99	7946	*
700	27.56	685	26.97	760	29.92	3.41	7.52	7947	*
750	29.53	735	28.94	810	31.89	*	*	*	*

Packing Unit – Sets per Box, all Lengths: 5

* on request